

Model : arle / spi / n2



100-277V 50-60Hz

TECHNICAL SPECIFICATION :

- LED WATT : 03W/06W/09W
- Single Color (CCT) : 2750k , 2950k , 4000k, 6000k
- Multi color : RGB
- Lumen / watt : 110 lm - 140 lm
- CRI > 80
- THD<10%
- PF>0.95
- LED Type : Emitter
- LED Make : Edison
- Available Beam Angle : 15°/25°/30°/45°/ 60°(Asymetric)
- Input Voltage : 220V AC / 12V DC
- Dimensions : 90 mm , H 220 mm
- IP (Ingress Protection) : IP 65 / 67 / 68
- Outdoor Casing : Aluminum Di-Cast
- Driver : Built In / Remote

PHOTOMETRIC**PRODUCT DESCRIPTION :**





- Luminaire housing & bracket made of die cast aluminium, aluminium & SS fasteners
- Toughened step extra clear safety glass 4mm is flushed
- Mounting bracket arrangement to facilitate easy installation at any desired location Swivel range of 0°-90°.
- Luminaire supplied with one metre cable length and a IP67 connector.
- Silicone gasket
- Sturdy construction in order to maintain performance of the luminaire and to reduce maintenance costs.
- Clear glass in the front with continuous rubber gasket to ensure adequate sealing against ingress of moisture, dust, insects etc.,
- Additional cable length to be ordered separately
- Wire for mains supply cable 2c×1.5mm²
- Dimming Option : Traic / Analog

Area of Application

Pathways, Parks, Sculptures, Gardens, Structures and Landscape lighting.

Available Finish

Standar White (On Demand Only)



C Range: 0 - 360DEG
C Interval: 10.00DEG
Test Speed: HIGH
Temperature: 25.3DEG

Range: 0 - 90DEG
Interval: 0.8DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.828m [K=1.0000]