

Model : arle / spi / n9

PRODUCT DESCRIPTION :

- Luminaries housing & bracket made of die cast aluminium, aluminium & SS fasteners
- Mounting earth spike or die-cast bracket arrangement to facilitate easy installation at any desired location.
- Luminaries supplied with one metre cable length and a IP67 connector.
- Silicone gasket for moisture protection
- Toughened step extra clear safety glass 4mm is flushed with SS trim to avoid dirt contamination
- Additional cable length to be ordered separately
- Sturdy construction in order to maintain performance of the luminaries and to reduce maintenance costs.
- Clear glass in the front with continuous rubber gasket to ensure adequate sealing against ingress of moisture, dust, insects etc.,
- Wire for mains supply cable 2c×1.5mm²
- Additional cable length to be ordered separately
- Dimming Option : Traic / Analog

Area of Application

Pathways, Parks, Sculptures, Gardens, Structures and Landscape lighting.


TECHNICAL SPECIFICATION :

- LED WATT : 07W
- Single Color (CCT) : 2750k , 2950k , 4000k, 6000k
- Multi color : RGB
- Lumen / watt : 110 lm - 140 lm
- CRI > 80
- THD<10%
- PF>0.95
- LED Type :COB
- LED Make : Edision / Nichia
- Available Beam Angle : 15°/30°/40°
- Input Voltage : 220V AC / 12V DC
- Dimensions : 80 mm , H mm
- IP (Ingress Protection) : IP 65 / 67
- Outdoor Casing : All. Dicast
- Driver : Built In / Remote z

Available Finish

Pure polyester powder coated

- Graphite grey
- Anthracite grey
- Jet black



PHOTOMETRIC

