


Model : arle / ing / k4



TECHNICAL SPECIFICATION :

- LED WATT : 12W / 24W/36W
- Single Color (CCT) : 2750k , 2950k , 4000k, 6000k
- Multi color : RGB
- Lumen / watt : 110 lm - 140 lm
- CRI > 80
- THD<10%
- PF>0.95
- LED Type : Emitter
- LED Make : Edison / Cree
- Available Beam Angle : 15°/25°/ 30°/45°/60° (Asymmetric Lens)
- Input Voltage : 12V / 24V AC/DC - 220V AC
- Dimensions : 150 mm , H 220 mm
- IP (Ingress Protection) : IP 65 / 67 / 68
- Outdoor Casing : PVC / Aluminum

PRODUCT DESCRIPTION :

- Inground directional up light for LED for mounting into concrete surface
- Available as a walk over or underwater application
- Construction - Body Made of SS -304 / SS-316 (Optional) grade.
- Extruded aluminium for better heatsink of LED
- Silicone gasket for moisture protection
- Toughened step extra clear safety glass 12 mm incorporated to avoid dirt contamination
- For walk over static load maximum 2 tons and for drive over maximum 5 tons @30km/hrs
- High temperature silicone cable length for IP-67 = 1mtr, for IP-68 = 3mtr with gland
- Additional cable length to be ordered separately

- Rubber H07RNF cable length for IP-67 = 1mtr, for IP-68 = 3mtr with gland
- Additional cable length to be ordered separately
- Wire for mains supply cable 3c×1.5mm²
- IP-68 fast connector integrated for cable O.D.6-10mm



PHOTOMETRIC

