


SQUARE UD

Model : arle / upd / s1

**TECHNICAL SPECIFICATION :**

- LED WATT : 09W /18W
- Single Color (CCT) : 2750k , 2950k , 4000k, 6000k
- Multi color : RGB
- Lumen / watt : 110 lm - 140 lm
- CRI > 80
- THD<10%
- PF>0.95
- LED Type : Emitter
- LED Make : Edision / CREE
- available Beam Angle : 15°/25°/30°/45°/60°(Asymetric lense)
- Input Voltage : 220V AC
- Dimensions : H - 127 mm
- IP (Ingress Protection) : IP 66 / 67
- Outdoor Casing : Die Cast Alluminium
- Driver : Built In / Remote

PRODUCT DESCRIPTION :

- Luminaire made of pressure die cast aluminium, extruded aluminium & non corrosive stainless steel fasteners.
- Clear toughened glass.
- Silicone gasket.
- Hybrid optics with lens & reflector combination for higher efficiency, lower optical losses with optimum glare suppression.
- Die Cast aluminium base for easy installation onto the wall / column.
- Cable entries for through-wiring of mains supply cable.
- Integral constant current power supply.


Area of Application

Residential, Building facade, Commercial centres, Passages, Pathways, Sculptures and Structures.

Product Benefits

Sturdy construction in order to maintain performance of the luminaire and to reduce maintenance costs.

- Quick & simple installation with low maintenance.
- Clear glass in the front with continuous silicone gasket to ensure adequate sealing.
- Sustainable LED technology offers durability and optimal light output with low power consumption.

**PHOTOMETRIC**